

# Technical Data Sheet

Ace Timberlac Series

## Description

Diamond Ace Timberlac Wood Stains enhances the beauty and shades of wooden products. Wood Stains is suitable for all types of interior wood, furniture, doors and windows.

## Recommended use

These are specially designed for coloring of wooden surfaces before applying Nitrocellulose, Polyester & Polyurethane finishes. It gives good light fastness & fast drying.

## Physical properties

Colour	Standard color range
Finish	Gloss
Solids (vol %)*	8 ± 2
Flash point	23 °C
Specific Gravity	0.88 ± 0.03

## Film Thickness and Spreading Rate

Film Thickness	10 microns dft
Spreading rate	8-10 (m <sup>2</sup> / Ltr/ Coat)

## Surface Preparation

Ensure that surface is clean, dry and free from grease, oil and other contamination.

## Application

Application Methods  Spray (airless or conventional) & MuslinCloth Pad

Cleaning Ace Timberlac Premium Thinner.

Thinning Not Required / Ready to use

## Drying Time

Temperature	Dry to Touch	Dry to Handle	Recoating Time
25 °C	5 mins.	10 mins.	20 mins.

## Ace Timberlac NC Wood Stains



## Storage

The product must be stored in accordance to the national regulations. The product should be kept in a well-ventilated place, protected from heat and direct sunlight. The containers must be kept tightly closed.

## Handling

Handle with care. Stir well before use.

## Packing Size

0.91 Ltr

## Health and Safety

Material health and safety data sheet is available upon request. Please observe the precautionary notice displayed on the container. Ensure proper ventilation during application and drying of paint. Avoid inhalation of paint mist and vapours and skin contact. Spillage of paint on skin should immediately be removed with suitable cleanser soap and water. Eyes should be well flushed with water and immediate medical attention should be sought.



The No. 1 Selling National Brand