

Technical Data Sheet

Timberlac Series

Description

Diamond Ace Timberlac Wood Stain is a ready-to-use product based on specific nitrocellulose resin. It can be easily applied to wood to give it various transparent colours.

Recommended Use

It is specially designed for application on various types of woods to give them a natural look, colour, and appearance. It is a fast-drying product with good light-fastness. It can be overcoated with Diamond Ace Timberlac Clear Varnish, NC Lacquer, PU Lacquer, or Acrylic Lacquer.

Physical Properties

Colour	Standard Colour as per shade card.
Finish	Smooth / Matt
Solids (vol %)	10 ± 2
Flash Point	22°C
Weight / Liter	0.88 Kg

Film Thickness and Spreading Rate

Recommended Dry Film Thickness	10-15 Micron /Coat
Theoretical spreading rate	8-12 (m ² /L/coat)

Surface Preparation

Before painting, surfaces must be dry, clean, and free from dirt, grease, rust, flaking paint, and other contaminants. Rusty metal or previously painted surfaces must be properly rubbed down with suitable sanding paper and dusted off before the application.

Application

Application Method:	Brush, Spray,
Thinner/Cleaner	Diamond Ace Timberlac Premium Thinner

Drying Time	
Touch Dry	10 – 15 Minutes
Recoating Time	1 Hour

Typical paint system

Diamond Ace Timberlac Sanding Sealer	2-3 Coats
Diamond Ace Timberlac Wood Stain	2-3 Coats
Diamond Ace Timberlac Lacquer	1 Coat

DISCLAIMER

The information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control, we cannot guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice.

Ace Timberlac Wood Stain



Storage

The product must be stored according to national regulations. It should be kept in a well-ventilated place, protected from heat and direct sunlight, and the containers must be kept tightly closed.

Handling

Handle with care. Stir well before use.

Packing Size

0.91 L

Health and Safety

Material health and safety data sheet is available upon request. Please observe the precautionary notice displayed on the container. Ensure proper ventilation during application. Avoid inhalation & skin contact. Spillage on skin should immediately be removed with suitable cleanser soap and water. Eyes should be well flushed with water and immediate medical attention should be sought.



Pakistan's No.1 Paint