Technical Data Sheet

Everlast

Description

Diamond Everlast Woodcoat Thinner is a high quality fast drying thinner designed to dilute nitrocellulose based Paint, Wood Lacquer, Matt Lacquer and Sanding Sealer.

Recommended Use

Designed to use as thinner for thinning Diamond Everlast High Gloss Enamel and Automotive paint to give rapid hardening & good adhesion

Physical Properties

Colour Clear
Finish NA
Solids (vol %)* NA
Flash Point 34 °C
Specific Gravity 0.80+/-0.02

Film Thickness and Spreading Rate

Spreading Rate (m² / l) NA

Surface Preparation NA

Everlast Woodcoat Thinner



Storage

The product must be stored in accordance to the national regulations. The product should be kept in a well-ventilated place, protected from the heat and direct sunlight. The containers must be kept tightly closed.

Handling

Handle with care. Stirr well before use.t.

Packing Size

0.91 Ltr, 3.64 Ltrs.

Health and Safety

Material health and safety data sheet is available upon request. Please observe the precautionary notice displayed on the container. Ensure proper ventilation during application and drying of paint. Avoid inhalation of paint mist/vapours and skin contact. Spillage of paint on skin should immediately be removed with suitable cleanser soap and water. Eyes should be well flushed with water and immediate medical attention should be sought.

