

# Technical Data Sheet

Overall Series

## Description

Diamond Overall Texture is a top quality water based paint used to produce different kinds of decorative textural effects and patterns.

## Recommended use

Recommended for interior use on plaster, concrete, gypsum, brickwork, asbestos etc. The product gives a variety of finishes depending on the type of roller used and application techniques.

## Physical properties

Colour	White
Finish	Depending on application technique
Solids (vol %)*	55 ± 2
Flash point	N/A – Water Based
Specific Gravity	1.70

## Film Thickness and Spreading Rate

Spreading rate	1.50–2.00 m <sup>2</sup> /kg/Coat
----------------	-----------------------------------

## Surface Preparation

All loose material including loose plaster, cement splashes, old paint, dust, etc. must be thoroughly removed. New plaster/ concrete must be fully cured.

## Condition during application

The temperature of the substrate should be min. 3°C above the dew point of the air temperature and relative humidity not more than 70% measured in the vicinity of the substrate. Good ventilation is necessary when the paint is used in confined spaces. Mix the paint to uniform consistency before application.

## Application

Application Method	Special Roller designed for texture application
Cleaning	Clean water
Thinning	Not Required / Ready to use

## Drying Time

Temperature	Dry to Touch	Dry to Handle	Recoating Time
25 °C	4 hours	8 hours	N/A
35 °C	3 hours	6 hours	N/A

## Typical paint system

### On Plaster / Concrete

Diamond Overall Wall Sealer	1 Coat
Diamond Overall Primer filler Putty	2 Coats
Diamond Overall Texture	1 Coat
Diamond ACE Plastic Emulsion	2 Coats

## Overall Texture



## Storage

The product must be stored in accordance to the national regulations. The product should be kept in a well-ventilated place, protected from heat and direct sunlight. The containers must be kept tightly closed.

## Handling

Handle with care.

## Packing Size

6 kgs and 24 kgs.

## Health and Safety

Material health and safety data sheet is available upon request. Please observe the precautionary notice displayed on the container. Ensure proper ventilation during application and drying of paint. Avoid inhalation of paint mist and vapours and skin contact. Spillage of paint on skin should immediately be removed with suitable cleanser soap and water. Eyes should be well flushed with water and immediate medical attention should be sought.



The No. 1 Selling National Brand