

Technical Data Sheet

Overall Series

Description

Diamond Overall Paint Remover removes air-dried, baking, polyurethane, epoxy paint and powder coated surface.

Recommended Use

Designed to use as general purpose paint remover for decorative, automotive & industrial applications.

Physical Properties

Colour	Clear
Finish	NA
Solids (vol %)*	NA
Specific Gravity	1.20 ± 0.02

Film Thickness and Spreading Rate

Spreading Rate	NA
----------------	----

Method of Use

1. Open the can slowly to avoid sudden pressure release.
2. If the painted surface is oily wash down with a degreasing solution or with warm water with dishwashing detergent.
3. Carefully pour a suitable quantity of paint remover into an open top container.
4. Apply thick coat of paint remover with soft brush & cover up that area.
5. Wait for paint to wrinkle, blister or soften for 10-15 minutes.
6. Remove all the paint with paint scrapper.
7. Finally wash down & clean the surfaces with water or methylated spirits.

Recoating	NA
-----------	----

Overall Paint Remover



Storage

The product must be stored in accordance to the national regulations. The product should be kept in a well-ventilated place, protected from the heat and direct sunlight. The containers must be kept tightly closed.

Handling

Handle with care. Stirr well before use.t.

Packing Size

0.75kg, 3kgs.

Health and Safety

Material health and safety data sheet is available upon request. Please observe the precautionary notice displayed on the container. Ensure proper ventilation during application and drying of paint. Avoid inhalation of paint mist/vapours and skin contact. Spillage of paint on skin should immediately be removed with suitable cleanser soap and water. Eyes should be well flushed with water and immediate medical attention should be sought.



Pakistan's No.1 Paint