Technical Data Sheet

Description

Value Emulsion is an economical emulsion paint with good application properties and a smooth matt finish. It can be applied on interior walls, ceilings, old concrete plaster, chipboard and hardboard.

Recommended use

Recommended for use on plaster, concrete, gypsum, brick work and asbestos surfaces. (For interior surfaces only).

Physical properties

Colour Standard Colour Range

Finish Matt 47 ± 2 Solids (vol %)*

Flash point N/A - Water Based

Specific Gravity 1.40 - 1.50

Film Thickness and Spreading Rate

Film Thickness 30 microns dft 12-14 (m²/ Ltr/Coat) Spreading rate

Surface Preparation

All loose material including loose plaster, cement splashes, old paint, dust, etc. must be thoroughly removed. New plaster/ concrete must be fully cured.

Application

Application Methods





Cleaning Clean water

Thinning 50 - 70% with Clean Water

Drying Time

Temperature	Dry to Touch	Dry to Handle	Recoating Time
25 °C	30 minutes	2 hours	3 hours
35 °C	15 minutes	1 hour	2 hours

Typical paint system

On Plaster / Concrete

Diamond Overall Wall Sealer 1 Coat Diamond Value Wall Putty 2 Coats Diamond Value Emulsion 3 Coats

Value **Emulsion**



Storage

The product must be stored in accordance to the national regulations. The product should be kept in a well-ventilated place, protected from heat and direct sunlight. The containers must be kept tightly closed.

Handling

Handle with care. Stir well before use.

Packing Size

0.91 Ltr, 3.64 Ltrs and 14.56 Ltrs.

Health and Safety

Material health and safety data sheet is available upon request. Please observe the precautionary notice displayed on the container. Ensure proper ventilation during application and drying of paint. Avoid inhalation of paint mist and vapours and skin contact. Spillage of paint on skin should immediately be removed with suitable cleanser soap and water. Eyes should be well flushed with water and immediate medical attention should be sought.

